

Proving & Retarding

Provers

BX Base prover



Description

The Mono BX base prover compliments our convection ovens and other auxillary equipment from our BX range. It can be used as a base prover underneath an oven or as a stand alone unit. the unit is mains water connected, so no need for manual filling of the unit. Operation is simple via a one touch waterfill button.

The BX base prover creates the perfect humid environment for your doughs.

Features

- Stainless steel
- Mobile - On castors
- Heavy duty construction
- Easy to clean
- Extendable tray support

Machine Reference

Reference	Model
FG177	Landscape BX Base prover
FG177	Portrait BX Base prover

Options

- Electronic 7 day Timer
- Glass doors

Dimensions:

Model	Landscape BX Base prover	Portrait BX Base prover
Height:	930mm	900mm
Width:	1000mm	780mm
Depth:	850mm	1065mm
Depth (with tray support):	1460mm	1525mm
Weight:	110kg	80kg
Noise	Less than 85 dB	Less than 85 dB
Power:	Double element; Single phase; 230V; 50hz; 2kW; 8.8 Amps	Single element; Single phase; 230V; 50hz; 1kW; 4.5 Amps

Capacity:

Number of trays:	16 trays	8, 10, 16 or 20 trays (Dependant on tray size used)
------------------	----------	---

Water supply:

Prover is supplied with a 1.0m long flexible hose with 3/4" B.S.P. female connectors on both ends. Water pressure required is 2 Bar - 6 Bar. (Standard domestic water pressure is usually within these parameters).

Customers are strongly advised to fit a water conditioning unit to the supply for this equipment. The unit should remove and not suspend water hardness. MONO can provide a unit suitable for this purpose. No drain is required with this Prover.

Convection oven configuration table

	BX 2 Tray 600 x 400mm	BX 4 Tray 600 x 400mm	BX 4 Tray 400 x 600mm	BX 4 Tray 400 x 800mm	BX 10 Tray 400 x 600mm	BX 10 Tray 400 x 800mm
Landscape tray orientation	•	•				
Portrait tray orientation			•	•	•	•



BX base prover with doors open



BX base prover extendable tray support



MONO Equipment • Swansea West Industrial Park • Queensway • SA5 4EB • UK.
 Tel: 01792 564000 (Sales) • +44 1792 564004 (International Sales)
 01792 561234 (Switchboard) • Fax: 01792 561016
 E-mail: sales@monoequip.com • www.monoequip.com

As it is our policy to improve our machines continuously, we reserve the right to change specifications without prior notice. 7445/indn/12.06