



Certificate number: 2401747 (1)

Issued 03/01/2024

Expires 03/01/2029

Kiwa Regulation 4 (KUKreg4) Certification

Evaluation Guideline – Kiwa UK – EG004 – Regulation 4(1)(a)

Model number(s) – see Appendix

MONO Equipment Ltd.

Kiwa Watertec declares that legitimate confidence exists in the products specified in this certificate and supplied by the above organisation be relied upon to comply with the Kiwa Evaluation Guideline referred above.

Which verifies the requirements of:

Regulation 4(1)a of the Water Supply (Water Fittings) Regulations 1999 England & Wales: 2009 Northern Ireland and 2014 Byelaws Scotland.

This certificate has been issued in accordance with the Kiwa regulations for product certification.

Signed on behalf of Kiwa Watertec

David Jay, Business Unit Manager – Authorised Signatory
Kiwa Watertec

Publication of this certificate is allowed.

Products are intended to be used in the UK only. For other countries, other (National) requirements will apply.

See <https://www.kiwa.com/gb/en/about-kiwa/water-products/> or the QR code below to ensure that the certificate is still valid.

CERTIFICATE

Kiwa Watertec
(A Trading Division of Kiwa Ltd)
26A Rassau Industrial Estate
Ebbw Vale
Gwent
NP23 5SD
United Kingdom
T +44 (0)1495 308185
uk.water@kiwa.com
www.kiwa.co.uk

Certificate Issued to:
MONO Equipment Ltd
Queensway
Swansea West Industrial Park
Swansea
SA5 4EB
United Kingdom



KUKreg4

Product Certificate

Appendix to Certificate number: 2401747

The following products belong to this certificate

<p>PRODUCT DESCRIPTION Range of atmospheric electronic steaming ovens. The water supply is controlled via a solenoid valve and is supplied via a plastic inlet hose. ATS3 – Without Production Surveillance.</p>
<p>MODEL(S) 134 7 Tray 60 x 40 138 7 Tray 40 x 60 139 7 Tray 18 x 30 148 3/4 Tray Compact 60 x 40 149 10 Tray 40 x 60 150 10 Tray 18 x 30 153 4/5 Tray 40 x 60 158 4/5 Tray 60 x 40 159 4/5 Tray 18 x 30 170 10 Tray 40 x 80 173 4 Tray 40 x 80 174 10 Tray (Wash) 60 x 40 175 4 Tray (Wash) 60 x 40 180 10 Tray 18 x 26 189 3/4 Tray 18 x 26 190 4 Tray 26 x 18</p>
<p>SIZE: 3/4" BSP captive nut.</p>
<p>SCOPE: Manufacturer recommended maximum working pressure 6 Bar & maximum operating temperature: Cold water supply only. Hygienic Purposes: Non-metallic materials suitable for continuous use with cold water only.</p>
<p>MARKING Mono equipment, address, model no, serial no and other technical information on data plate. Mono on front casing.</p>
<p>MATERIALS Non-metallic materials assessed (BS6920) to point of discharge/to backflow prevention device.</p>
<p>BACKFLOW PROTECTION NOTES A compliant double check valve or some other no less effective device providing backflow prevention protection to at least fluid category three shall be fitted at the point of connection(s) between the water supply and the fitting or appliance. Discharge to drain must be via a Type AA, AB or AD air gap or in accordance with EN 1717.</p>
<p>ADDITIONAL NOTES Opacity cannot be guaranteed at inlet hoses.</p>

Extra Notes