

The baker's Mechanical water meter



HAPPY CUSTOMERS

- Excellent bread quality due to a perfectly mixed dough at the right temperature.

SUPPLIED COMPLETE

- With inlet kit(s) and fittings
- Hose with hanger for the mixer.



PRACTICAL

- Easily and quickly installed by a plumber.
- It does not need to be watched.

TIME SAVED

- You preset the litres needed.
- The meter measures and stops automatically.

THE TEMPERATURE MIXING VALVE
SPÉCIAL LOW TEMPERATURES



The knob with huge graduations by one degree guarantees excellent accuracy with precise setting between 1 and 40 degrees.

The Economical Accuracy

WHICH STOPPIL WATER METER CHOOSE?



SA-PC

DIAL SETTING

Most simple - just push the dial up to the litres you wish to flow, precisely thanks to a click-and-ratchet mechanism every 0,5 l between 10 and 100 litres.

3 WAYS OF TEMPERATURE MIXING

(temperature check on a gauge).

SA

No temperature mixing

1 inlet - cold only.
Pressure required : 0,15 bar.

Suitable for direct connection to a chiller, the bottom of which has to be positioned at minimum 1 m 50 higher than the meter.

SAMM

Manual temperature mixing

2 inlets - hot and cold.
Pressure required : 0,2 bar.

If connected to a chiller, the bottom of it has to be fitted at minimum 2 m higher than the meter.

If this is not possible, we recommend for a quicker flow and better accuracy to fit a pump on the pipe after the existing chiller and a contact on the meter or EVEN BETTER, use OUR chiller working with city pressure and therefore requiring no accessory whatever.

SAMT

Automatic temperature mixing by means of a thermostatic control particularly suitable for very cold water

2 inlets - hot and cold.
Pressure required : 1 bar.

The thermostat allows a very precise and fast temperature setting between 1 and 40 degrees and maintains the temperature at the degree required throughout the day.

If connected to an existing chiller, a pump after the chiller and a contact on the meter becomes necessary or EVEN BETTER, use OUR chiller working with city pressure and therefore requiring no accessory whatever.



SAMM-PC



SAMT-PC

This brochure is subject to change and therefore not contractual